



D/I-PEG

STANDARD PRODUCT SPECIFICATIONS

DIMENSION:

48”L x 14.3”W x 4.87”H

Materials:

Die-Formed Heavy Gauge Prepainted Cold-Rolled Steel Housing

Finish:

Powder Coated

Lens:

22 ga. Cold-Rolled Steel w/ 5/64” Diameter Micro Perforations at Staggered 7/64” Baffle w/ White Opal Acrylic Diffuser. - Options Shown Below

Lamps:

Lamps are Sold Separately

Listing:

Dry Listed

Ballast Info:

120 Volt Class P, 60 Hz. Electronic, Options Shown Below.

Installation:

Hardware is Included. Install by a Qualified Electrician.

Warranty:

1 Year Limited From Date of Shipment



**LAMPS SOLD SEPARATELY - ADD AS SEPARATE LINE ITEM
SEE THE LAMPS SPECSHEET FOR ORDER CODES**

EXAMPLE: DL-D/I-PEG-WH-232EH-4-AC12-PER-EM

MODEL	FINISH	WATTAGE	BALLAST	LENGTH	MOUNT	LENS/REFL
D/I-PEG	WH White CC Custom Color	232 2-F32 T8	EN Hybrid Electronic ER Residential Electronic EH Commercial Electronic	4 4 Feet 8 8 Feet 12 12 Feet 16 16 Feet	AC XX Aircraft Cable PD XX Pendant Replace XX With Desired Length of Mount	PER Perferated SW Smooth White FLU Fluted
			The 'EH' Ballast is Dual Voltage 120v/277v HPF	Runs available in increments of 4 feet		OPTIONS EM Emergency Ballast