



D/I-PERF

STANDARD PRODUCT SPECIFICATIONS

DIMENSION:
48”L x 11”W x 4”H

Materials:
Die-Formed Heavy Gauge Prepainted Cold-Rolled Steel Housing

Finish:
Powder Coated

Lens:
22 ga. Cold-Rolled Steel w/ 5/64” Diameter Micro Perforations at Staggered 7/64” Baffle w/ .020 White Opal Acrylic Diffuser.

Lamps:
Lamps are Sold Separately

Listing:
Dry Listed

Ballast Info:
120 Volt Class P, 60 Hz. Electronic, Options Shown Below.

Installation:
Hardware is Included. Install by a Qualified Electrician.

Warranty:
1 Year Limited From Date of Shipment



LAMPS SOLD SEPARATELY - ADD AS SEPARATE LINE ITEM
SEE THE LAMPS SPECSHEET FOR ORDER CODES

EXAMPLE: DL-D/I-PERF-WH-332EH-4-AC12

MODEL	FINISH	WATTAGE	BALLAST	LENGTH	MOUNT	OPTIONS
D/I-PERF	WH White CC Custom Color	332 3-F32 T8	EN Hybrid Electronic ER Residential Electronic EH Commercial Electronic The 'EH' Ballast is Dual Voltage 120v/277v HPF	4 4 Feet 8 8 Feet 12 12 Feet 16 16 Feet Runs available in increments of 4 feet	AC XX Aircraft Cable PD XX Pendant Replace XX With Desired Length of Mount	EM Emergency Ballast