



# D/I-URB

## STANDARD PRODUCT SPECIFICATIONS

DIMENSION:  
48”L x 12.2”W x 5.15”H

- Materials:**  
Die-Formed Heavy Gauge Prepainted Cold-Rolled Steel Housing
- Finish:**  
Powder Coated
- Lens:**  
22 ga. Cold-Rolled Steel w/ 5/64” Diameter Micro Perforations at Staggered 7/64” Baffle w/ White Opal Acrylic Diffuser.
- Lamps:**  
Lamps are Sold Separately
- Listing:**  
Dry Listed
- Ballast Info:**  
120 Volt Class P, 60 Hz. Electronic, Options Shown Below.
- Installation:**  
Hardware is Included. Install by a Qualified Electrician.
- Warranty:**  
1 Year Limited From Date of Shipment



LAMPS SOLD SEPARATELY - ADD AS SEPARATE LINE ITEM  
SEE THE LAMPS SPECSHEET FOR ORDER CODES

**EXAMPLE: DL-D/I-URB-WH-232EH-4-AC12-SW-EM**

MODEL	FINISH	WATTAGE	BALLAST	LENGTH	MOUNT	LENS/REFL
D/I-URB	WH White CC Custom Color	232 2-F32 T8	EN Hybrid Electronic	4 4 Feet	AC <del>XX</del> Aircraft Cable PD <del>XX</del> Pendant  Replace <del>XX</del> With Desired Length of Mount	PER Perferated
			ER Residential Electronic	8 8 Feet		SW Smooth White
			EH Commercial Electronic	12 12 Feet 16 16 Feet		FLU Fluted
			The 'EH' Ballast is Dual Voltage 120v/277v HPF	Runs available in increments of 4 feet	OPTIONS	
						EM Emergency Ballast