



## **Standard Product Specifications**

Materials: Steel Housing Finish: Post-Painted

Lens:

Frosted Acrylic

**LED:** Integrated LED Array

Listing:

Damp List to Meet UL 1598 Standard **Driver Info:** 

120/277V

20/277V

0-10V Dimming Standard

**Installation Information:** Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

## **DIMENSIONS:**

2' - 22.20"L x 2.36"W x 2.64"H 4' - 47.3"L x 2.36"W x 2.64"H

8' - 94.17"L x 2.36"W x 2.64"H





MODEL	FINISH	LENGTH	WATTAGE	KELVIN
Model 4802L	Finish WH- White	Length 2 - 2 Feet 4 - 4 Feet 8 - 8 Feet	\text{Wattage(2')} CCT Adjustable 15/20/25W; 35/40/50K \text{Wattage(4')} CCT Adjustable 18/28/44W; 35/40/50K \text{Wattage(8')} CCT Adjustable 54/75/90W; 30/40/50K	<b>Kelvin 35</b> - 35K <b>40</b> - 40K <b>50</b> - 50K

Divine Lighting Fabrication & Powder Coating, LLC. Conroe, TX

http://www.divinelighting.net customerservice@divinelighting.net PH: 936-494-3900 FX: 936-494-3910