

POST TOP/WALL MOUNT CK-SERIES

DIVINE LIGHTING
FABRICATION & POWDER COATING LLC

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

White Plastic w/ Microstructure Injection
Molded Lens

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

19.7" Dia. x 4.3"H

(Does Not Include Arm Dimensions)



CKPT



CKWM



CKSA



CKDSA

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
<u>Model</u> CKPT CKWM CKSA CKDSA	<u>Finish</u> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<u>Wattage</u> LED40 - 40W LED 4000 Lms LED60 - 60W LED 6000 Lms LED80 - 80W LED 8000 Lms LED100 - 100W LED 10000 Lms LED120 - 120W LED 12000 Lms LED150 - 150W LED 15000 Lms	<u>Kelvin</u> 30 - 30K 40 - 40K 50 - 50K	<u>Options</u> DIM - 0-10V Dimmable MOT - Motion Sensing EM16 - 1600 Lms Emergency HSS - House Side Shield

Divine Lighting Fabrication & Powder Coating, LLC.
Conroe, TX

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 12424 1030 ACE