

POST TOPS DHPT SERIES

DIVINE LIGHTING
FABRICATION & POWDER COATING LLC

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

Clear Polycarbonate

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Photocell Standard

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

DHPTS - 12.44"Dia. x 6.97"H

DHPTL - 16.54"Dia. x 7.6"H



MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model DHPTS DHPTL	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(DHPTS) LED60 - 60W LED 7800 Lms LED80 - 80W LED 10400 Lms LED100 - 100W LED 13000 Lms Wattage(DHPTL) LED120 - 120W LED 15600 Lms LED150 - 150W LED 19500 Lms LED200 - 200W LED 26000 Lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Options CCT - CCT Adjustable Dial

Divine Lighting Fabrication & Powder Coating, LLC.
Conroe, TX

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 102423 1240 ACE