



## Standard Product Specifications

Materials: Extruded Aluminum Finish: Powder Coated Lens: White Polycarbonate LED: Integrated LED Array Listing: Wet List to Meet UL 1598 Standard Driver Info: 120/277V Installation Information: Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

## **DIMENSIONS:**

6"W x 4"H x 20"E 6"W x 4"H x 44"E Backplate Dimensions: 7"W x 12"H

(Custom Extensions Available - Call Customer Service)





MODEL	FINISH	WATTAGE	KELVIN	EXTENSION	OPTIONS
Model DWM46S	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED22 - 22W LED 2500 Lms LED40 - 40W LED 5000 Lms	<u>Kelvin</u> 30 - 30K 40 - 40K 50 - 50K	Extension 20 - 20" 44 - 44" XX - Custom Extension in Inches	Options DIM - 0-10V Dimmable PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency MOT50 - Motion Sensing
Divine Lighting Fabrication & Powder Coating, LLC. http://www.divinelighting.net   Conroe, TX customerservice@divinelighting.net					PH: 936-494-3900 FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice