POST TOP EPTS101B



Standard Product Specifications

Materials: Die-Cast Aluminum Finish: Powder Coated Lens: Clear Polycarbonate LED: Integrated LED Array

Listing: Wet List to Meet UL 1598 Standard Driver Info: 120/277V Installation Information: Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

DIMENSIONS: 15.75"Dia. x 23.19"H



REV 121922-0933-JCE



EPA Rating: .69 Mounts on 2 3/8" Tenon

MODEL	FINISH	WATTAGE	KELVIN	LENS	TYPE	OPTIONS
Model EPTS101B	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED25 - 25W LED 2500Lms LED35 - 35W LED 3500Lms LED60 - 60W LED 6000Lms LED80 - 80W LED 8000Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Lens CP - Clear Polycarbonate FP - Frosted Polycarbonate* *Only available without optics	Type (CP Only) II - Type II III - Type III IV - Type IV V - Type V	Options DIM - 0-10V Dimmable PC - Photocell MOT - Motion Sensor
Divine Lighting Fabrication & Powder Coating, LLC. http://www.divinelighting.net Conroe, TX customerservice@divinelighting.net						36-494-3900 36-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice