

WALL SCONCES L SERIES

Standard Product Specifications

Materials:
20ga. G90 Galvanized Steel

Finish:
Powder Coated

Lens:
Polycarbonate Options

LED:
Integrated LED Array

Listing:
Damp List to Meet UL 1598 Standard

Driver Info:
120V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment

DIMENSIONS:

33 - 3"W x 3"H
34 - 3"W x 4"H
44 - 4"W x 4"H
45 - 4"W x 5"H

Lengths:

2' - 24" 3' - 35" 4' - 46"

(Custom Lengths Available - Call Customer Service)



MODEL	DIMENSIONS	FINISH	WATTAGE	KELVIN	LENS	LENGTH	OPTIONS
Model LUD - Up/Down LDN - Down LUP - Up	Dimensions 33 34 44 45	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(24") LED21 - 21W LED 2100 Lms LED36 - 36W LED 3600 Lms Wattage(35") LED21 - 21W LED 2100 Lms LED52 - 52W LED 5200 Lms Wattage(46") LED40 - 40W LED 4000 Lms LED64 - 64W LED 6400 Lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Lens WP - White Polycarbonate FP - Frosted Polycarbonate	Length 2 - 24" Length 3 - 35" Length 4 - 46" Length XX - Custom Length in Feet	Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency