

ADDRESS AND MAIL LIGHTING LINEAR ADDRESS LIGHT

DIVINE LIGHTING
FABRICATION & POWDER COATING LLC

Standard Product Specifications

Materials:

Aluminum Housing with Galvanized
Steel Back Plate

Finish:

Powder Coated

Lens:

White Acrylic

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

4"W x 30"H x 2.5"H

Number Height - 1.5"H

(Custom Sizes Available - Call Customer Service)



MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model LAL	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED5 - 5W LED 500 Lms LED10 - 10W LED 1000 Lms LED15 - 15W LED 1500 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency BRAILLE - Braille

Divine Lighting Fabrication & Powder Coating, LLC.
Conroe, TX

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 20723 1325 ACE