



Standard Product Specifications

Materials:

Composite Plastic Construction

Finish:

Built-In Finish

Lens:

Polycarbonate Options

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

MANWM-OB - 10.5"H x 6"W x 6.5"E **MANWM-LT** - 28.5"H x 10"W x 10.5"E

MAN-ST - 20"H x 10"W x 10.5"E









Shown With Long Tail



Shown With Lens Bottom and House Side Shield

MODEL	FINISH	WATTAGE	KELVIN	LENS	OPTIONS
26.11	71.11		** 1 .	-	
Model MANWM	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED20 - 20W LED 2200 Lms LED36 - 36W LED 3600 Lms SINC - Incandescent Socket	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Lens CP - Clear Polycarbonate FP - Frosted Polycarbonate	Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable PC - Photocell LT - Long Tail OB - Open Bottom ST - Short Tail HSS180 - 180 Degree House Side Shield