SITE LIGHTING **MSL SERIES**



Standard Product Specifications

Materials: Cast Aluminum Housing Finish: Powder Coated Lens: Clear Flat Glass LED: Integrated LED Array Listing: Wet List to Meet UL 1598 Standard Driver Info: 120/277V Installation Information: Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

DIMENSIONS:

MSLS - 9.25"W x 12.6"L x 3.3"H MSLM - 12.25"W x 15"L x 3.3"H MSLL - 12.25"W x 23"L x 3.3"H

(Does Not Include Mounting Arms)





MSLS



MSLM



MSLL



Pole Mount



Shield



Knuckle

MODEL	FINISH	WATTAGE	KELVIN	TYPES	OPTIONS
Model MSLS MSLM MSLL	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage(MSLS) LED75 - 75W LED 9600 Lms LED100 - 100W LED 13800 Lms LED120 - 120W LED 15600 Lms Wattage(MSLM) LED200 - 200W LED 20500 Lms LED200 - 200W LED 26000 Lms Wattage(MSLL) LED240 - 240W LED 34700 Lms LED320 - 320W LED 40000 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	<u>Types</u> III - Type III IV - Type IV V - Type V	Options PC - Photocell WM - Wall Mount KNL - Knuckle Mount MA - Mounting Arm MOT50 - Motion Sensing MOT50SP - Motion Special Programming HSS - House Side Shield FULLHSS - Full House Side Shield
Divine Lighting Fabrication & Powder Coating, LLC. http://www.divinelighting.net					PH: 936-494-3900

Divine Lighting Fabrication & Powder Coating, LLC Conroe, TX http://www.divinelighting.net customerservice@divinelighting.net PH: 936-494-3900 FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 20923 1450 ACE