

**LINEAR
LVR**



DIMENSIONS:
48”L x 10.5”W x 4”H

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:
Ambient Lighting for an Office or Hall. Downlight Only

Materials:
Extruded Aluminum

Finish:
Powder Coated

Lens:
Louver Reflectors

LED:
Integrated LED Array

Listing:
Dry List to Meet UL 1598 Standard

Driver Info:
120V

Installation Information:
Install by Qualified Electrician

Warranty:
1 Years From Date of Shipment



ORDER INFORMATION
Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	LENGTH	OPTIONS
Model D/I-LVR	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED36 - 36W LED 3600 Lms LED64 - 64W LED 6400 Lms Wattage (fluorescent) 232 - 4 - F32T8 (ER/EH 120 /120/277V)	Kelvin 30 - 30K 35 - 35K 40 - 40K	Length Multiples of 4' 4 - 4 Foot XX - Multiples of 4 Foot	Options DV - Dual Volt 120/277V MOT - Motion Sensor DIM - Dimmable 0-10V EM5 - 500Lms Emergency Backup EM7 - 700Lms Emergency Backup EM12 - 1200 Lms Emergency Backup EM14 - 1400Lms Emergency Backup AC50 - 50” Aircraft Cable EM7 and EM14 in Flourecent Only