

POST TOPS

QHR20

DIVINE LIGHTING

FABRICATION & POWDER COATING LLC

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

See Options Below

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

0-10V Dimmable Standard

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

16.25"L x 16.25"W x 24.75"H



Shown w/ Type V LumaLens



Shown w/ Open Frame; Full Cutoff

Lumen Table

*Available Lumens Based on Kelvin Selected

| | 19W | 36W | 53W | 80W |
|-------------------|-------------|-------------|-------------|---------------|
| Type I | x | x | x | 9,058-9,714 |
| Type II | 3,334-3,575 | 4,211-4,516 | 6,317-6,774 | 9,534-10,224 |
| Type III | 3,412-3,658 | 4,309-4,621 | 6,464-6,931 | 9,933-10,652 |
| Type IV | 3,482-3,734 | 4,398-4,717 | 6,597-7,075 | 9,920-10,652 |
| Type V Open Frame | 3,580-3,839 | 4,522-4,850 | 6,783-7,274 | 10,527-11,289 |
| Type V LumaLens | 1,992-2,136 | 3,774-4,047 | 5,556-5,958 | 8,386-8,993 |

| MODEL | FINISH | WATTAGE | KELVIN | LENS | TYPE | OPTIONS |
|-----------------------|---|--|---|---|---|--|
| Model QHR20 | Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color | Wattage LED19 - 19W LED36 - 36W LED53 - 53W LED80 - 80W | Kelvin 30 - 30K 40 - 40K 50 - 50K | Lens OP - Open Frame Full Cutoff PC - Polycarbonate Opal LumaLens (Type V Only) | Type I - Type I* *80W Only II - Type II III - Type III IV - Type IV V - Type V | Options PC - Photocell MOT - Motion Sensing EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency |

Divine Lighting Fabrication & Powder Coating, LLC.
Conroe, TX

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 83123 1430 ACE