

POST TOPS
QPT12Q

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

Clear Polycarbonate

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

0-10V Dimmable Standard

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

11.5"W x 17.5"H

10.5" Head Diameter



Lumen Table

*Available Lumens Based on Kelvin Selected

	10W	19W	28W
Type II	833-893	1,666-1,787	2,499-2,680
Type III	876-939	1,752-1,879	2,628-2,818
Type IV	867-930	1,735-1,860	2,602-2,790
Type V	918-984	1,836-1,968	2,753-2,952

MODEL	FINISH	WATTAGE	KELVIN	TYPE	OPTIONS
<u>Model</u> QPT12Q	<u>Finish</u> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<u>Wattage</u> LED10 - 10W LED LED19 - 19W LED LED28 - 28W LED	<u>Kelvin</u> 30 - 30K 40 - 40K 50 - 50K	<u>Type</u> II - Type II III - Type III IV - Type IV V - Type V	<u>Options</u> PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency