POST TOPS QRRPT SERIES



Standard Product Specifications

Materials:

Die-Cast Aluminum Housing Finish: Powder Coated Lens: Clear Polycarbonate LED: Integrated LED Array

Listing: Wet List to Meet UL 1598 Standard Driver Info: 120/277V Installation Information: Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

DIMENSIONS: QRRPTS/QRRPTS-C - 17"Dia. x 15"H QRRPTL/QRRPTL-C - 27"Dia. x 20"H





QRRPTL



QRRPTS-C



QRRPTL-C

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model QRRPTS QRRPTS-C QRRPTL QRRPTL-C	<u>Finish</u> DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage(QRRPTS & QRRPTS-C)LED84 - 84W LED 8000 LmsWattage(QRRPTL & QRRPTL-C)LED176 - 176W LED 16500 Lms	<u>Kelvin</u> 30 - 30K 40 - 40K 50 - 50K	Options PC - Photocell
Divine Lighting Fabrication & Powder Coating, LLC. Conroe, TX		http://www.divinelighting.net customerservice@divinelighting.net		PH: 936-494-3900 FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice