

CANOPY AND GARAGE LIGHTING

QSC30/QLC32

DIVINE LIGHTING
FABRICATION & POWDER COATING LLC

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

Clear Prismatic Acrylic

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

QSC30 - 16.125"W x 5.5"H

QLC32 - 26.75"W x 6"H



QSC30



QLC32

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
<u>Model</u> QSC30 QLC32	<u>Finish</u> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<u>Wattage(QSC30)</u> LED37 - 37W LED 3100 Lms LED65 - 65W LED 5500 Lms LED84 - 84W LED 6800-7800 Lms <u>Wattage(QLC32)</u> LED100 - 100W LED 8800 Lms LED176 - 176W LED 15400-17400 Lms	<u>Kelvin</u> 30 - 30K* <i>*Available Only with LED84 & LED176</i> 40 - 40K 50 - 50K	<u>Options</u> DIM - 0-10V Dimmable MOT - Motion Sensing PMXX - Pendant Mount Replace XX with Pendant Length in Inches

Divine Lighting Fabrication & Powder Coating, LLC.
Conroe, TX

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 21823 1155 ACE