

Standard Product Specifications

**Materials:**

Cast Aluminum Houston

**Finish:**

Powder Coated

**Lens:**

Clear Polycarbonate

**LED:**

Integrated LED Array

**Listing:**

Wet List to Meet UL 1598 Standard

**Driver Info:**

120/277V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS:**

18"Dia. x 18.75"H



QSL31PT



QSL32PT

MODEL	FINISH	WATTAGE	KELVIN	TYPE	OPTIONS
<b>Model</b> QSL31PT QSL32PT	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage</b> LED37 - 37W LED 5400 Lms LED65 - 65W LED 9600 Lms LED100 - 100W LED 14800 Lms LED140 - 140W LED 20000 Lms <i>*Lower lumen output on type IV</i>	<b>Kelvin</b> 30 - 30K* 40 - 40K 50 - 50K <i>*37W &amp; 65W Only</i>	<b>Type</b> II - Type 2 III - Type 3 IV - Type 4 V - Type 5	<b>Options</b> DIM0-10 - 0-10V Dimmable MOT - Motion Sensor PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency