

Standard Product Specifications

**Materials:**  
Die-Cast Aluminum Housing  
**Finish:**  
Powder Coated  
**Lens:**  
See Options Below  
**LED:**  
Integrated LED Array

**Listing:**  
Wet List to Meet UL 1598 Standard  
**Driver Info:**  
120/277V  
**0-10V Dimmable Standard**  
**Installation Information:**  
Install by Qualified Electrician  
**Warranty:**  
2 Years From Date of Shipment

**DIMENSIONS:**  
21”Dia. x 27.75”H



**Lumen Table**

\*Available Lumens Based on Kelvin Selected

	37W	65W	100W	140W
Type I	3,422-3,671	6,013-6,449	9,549-9,922	13,369-13,890
Type II	3,728-3,999	6,549-7,024	10,401-10,807	14,562-15,129
Type III	3,873-4,154	6,804-7,298	10,806-11,227	12,128-15,718
Type IV	3,986-4,276	7,004-7,512	11,123-11,556	15,572-16,178
Type V	4,045-4,338	7,106-7,621	11,285-11,725	15,799-16,415
Type V With LumaLens	2,604-2,793	4,575-4,907	7,266-7,550	10,173-10,569

MODEL	FINISH	WATTAGE	KELVIN	TYPE	LENS	OPTIONS
<b>Model</b> QWM21Q	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage</b> LED37 - 37W LED LED65 - 65W LED LED100 - 100W LED LED140 - 140W LED	<b>Kelvin</b> 30 - 30K 40 - 40K 50 - 50K	<b>Type</b> I - Type I II - Type II III - Type III IV - Type IV V - Type V	<b>Lens</b> CP - Clear Polycarbonate PC - Polycarbonate Opal Lumalens* *Type V Only	<b>Options</b> PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency