

Standard Product Specifications

Materials:

Extruded Aluminum Housing

Finish:

Powder Coated

Lens:

White Acrylic

LED:

Integrated LED Array

Listing:

Damp List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

UCSL8 - 8"L x 5"W x 1"E

UCSL12 - 12"L x 5"W x 1"E

UCSL18 - 18"L x 5"W x 1"E

UCSL24 - 24"L x 5"W x 1"E

UCSL32 - 32"L x 5"W x 1"E



UCSL8 on overstock! Please refer to the UCSL8-OVERSTOCK cutsheet

MODEL	FINISH	WATTAGE	KELVIN	LENS	OPTIONS
Model UCSL8 *overstock item* UCSL12 UCSL18 UCSL24 UCSL32	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage (UCSL8) LED3 - 3W LED 250 Lms Wattage (UCSL12) LED5 - 5W LED 400 Lms Wattage (UCSL18) LED8 - 8W LED 600 Lms Wattage (UCSL24) LED12 - 8W LED 800 Lms Wattage (UCSL32) LED15 - 15W LED 1350 Lms	Kelvin 30 - 30K	Lens WA - White Acrylic	Options DIM - Triac-dimmable OFS - On Off Switch Included