

**CEILING FLUSH  
1212M**

Standard Product Specifications

**Materials:**

20ga. G90 Galvanized Steel Pan

**Finish:**

Powder Coated

**Lens:**

Polycarbonate Options

**LED:**

Integrated LED Array

**Listing:**

Damp List to Meet UL 1598 Standard

**Driver Info:**

120V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS:**

**1212M** - 12”Sq. x 4.25”D (Not ADA)

**1212MS** - 12”Sq. x 4”D (ADA)



MODEL	FINISH	WATTAGE	KELVIN	LENS	OPTIONS
<b>Model</b> 1212M 1212MS	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	<b>Wattage</b> LED20 - 20W LED 2000 Lms	<b>Kelvin</b> 30 - 30K 35 - 35K 40 - 40K 50 - 50K	<b>Lens</b> WP - White Polycarbonate FP - Frosted Polycarbonate	<b>Options</b> DV - Dual Volt 120/277V DIM - 0-10V Dimmable PC - Photocell MOT - Motion Sensing EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency