

Standard Product Specifications

Materials:

Aluminum Housing
Stainless Steel Options Available

Finish:

Powder Coated

Lens:

Clear Acrylic

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

6" Dia. x 42"H

Custom Heights Available



DARK SKY
COMPLIANT



BODL



BOFL



DIRECT BURY EXTENSION

| MODEL | FINISH | WATTAGE | KELVIN | HEIGHT | OPTIONS |
|------------------------------|--|--|---|--|---|
| Model BODL BOFL | Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color | Wattage LED15 - 15W LED 1500 Lms | Kelvin 30 - 30K 40 - 40K 50 - 50K | Height 42 - 42"H XX - Custom Height | Options DIM - 0-10V Dimmable HSS90 - House Side Shield 90 Degrees HSS180 - House Side Shield 180 Degrees EM5 - 500 Lms Emergency Backup EM12 - 1200 Lms Emergency Backup DBE - Direct Bury Extension PC - Photocell |