

Standard Product Specifications

- Materials:**
Die-Cast and Extruded Aluminum

Finish:
Powder Coated

Lens:
Clear Polycarbonate

LED:
Integrated LED Array
- Listing:**
Wet List to Meet UL 1598 Standard

Driver Info:
120V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment

DIMENSIONS:
7.75”Dia.
Available Heights: 12”, 20”, 32”, 38”.



| MODEL | FINISH | WATTAGE | KELVIN | HEIGHT | OPTIONS |
|------------------------|---|--|---|---|--|
| <u>Model</u> BOL045 | <u>Finish</u> DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color | <u>Wattage</u> LED10 - 10W LED 1000 Lms LED14 - 14W LED 1400 Lms LED20 - 20W LED 2000 Lms LED24 - 24W LED 2400 Lms LED30 - 30W LED 3000 Lms | <u>Kelvin</u> 30 - 30K 40 - 40K 50 - 50K | <u>Height</u> 12” 20” 32” 38” | <u>Options</u> DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM4 - 400 Lms Emergency EM10 - 1000 Lms Emergency EM12 - 1200 Lms Emergency PC - Photocell |