

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

White Plastic w/ Microstructure Injection
Molded Lens

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

19.7"Dia. x 4.3"H



CKGL (Ceiling Mounted)



CKGL (Pendant Mounted)

MODEL	FINISH	WATTAGE	KELVIN	MOUNT	OPTIONS
Model CKGL	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED40 - 40W LED 4000 Lms LED60 - 60W LED 6000 Lms LED80 - 80W LED 8000 Lms LED100 - 100W LED 10000 Lms LED120 - 120W LED 12000 Lms LED150 - 150W LED 15000 Lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Mount CM - Ceiling Mount PMXX - Pendant Mount Replace XX with Pendant Length in Inches	Options DIM - 0-10V Dimmable MOT - Motion Sensing EM16 - 1600 Lms Emergency HSS - House Side Shield