

LINEAR DILPF/DILPC

Standard Product Specifications

Materials:
Heavy Gauge Cold-Rolled Pressed Steel

Finish:
Powder Coated

Lens:
White Opal Acrylic Diffuser

LED:
Integrated LED Array

Listing:
Dry List to Meet UL 1598 Standard

Driver Info:
120/277V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment

DIMENSIONS:

LPF - 48”L x 9.625”W x 3.25”H

LCP - 48”L x 7.75”W x 2.5”H



LCP
Shown with Optional Outer Perforations



LPF
Shown with Optional Outer and Top Perforations

Also Available in LED Tube Lamps

MODEL	FINISH	LENGTH	WATTAGE	KELVIN	OUTER ROW	CENTER ROW	TOP ROW*	OPTIONS
							*LPF Only	
Model DILPF DILPC	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Length 4 - 4 Foot XX - Custom Length* *Multiples of 4 Foot	Wattage LED64 - 64W LED 6400 Lms LED72 - 72W LED 7200 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Outer Row Smooth Sides (Standard) SPER - Sides Perforated	Center Row LOUV - Louvered LENS - Smooth White Lens	Top Row Smooth Sides (Standard) TPER - TPerforated	Options DIM - 0-10V Dimmable MOT - Motion Sensing EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency ACXX - AC Cable Mount *Replace XX with Length in Inches