

LINEAR DILPS/DILPB

Standard Product Specifications

Materials:
Heavy Gauge Cold-Rolled Pressed Steel

Finish:
Powder Coated

Lens:
White Opal Acrylic Diffuser

LED:
Integrated LED Array

Listing:
Dry List to Meet UL 1598 Standard

Driver Info:
120V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment

DIMENSIONS:

7.75"W x 2"H x 48"L
7.75"W x 2"H x **XX**"L (Custom Length)



Also Available in LED Tube Lamps



LOUVERED



LPB



LPS



PERFORATED

MODEL	FINISH	LENGTH	WATTAGE	KELVIN	OUTER ROW	MOUNT	OPTIONS
Model DILPS DILPB	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Length 4 - 4 Foot XX - Custom Length* *Multiples of 4 Foot	Wattage LED64 - 64W LED 6400 Lms LED128 - 128W LED 12800 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Outer Row(Sides) PER - Perforated LV - Louvered* <i>*Type V Only</i>	Mount AC50 - 50" Aircraft Cable Mount PMXX - Pendant Mount Replace XX with Length of Pendant Rods in Inches	Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable MOT - Motion Sensing EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency