

DIRECT / INDIRECT

D/I-LPS & D/I-LPB



DIMENSIONS:
48”L x 7.75”W x 2”H

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Ambient Lighting For an Office or Task Area

Materials:

Heavy Gauge Cold-Rolled Steel Housing

Finish:

Powder Coated

Lens:

White Opal Acrylic Diffuser

LED:

Integrated LED Array

Listing:

Dry List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:


2 Years From Date of Shipment




LPB



LPS



LV
Louvered



PER
Perforated

Also available in LED tube lamps

ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	MOUNT	OUTER ROW	LENGTH	OPTIONS
Model D/I-LPB D/I-LPS	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED64 - 64W LED 6400 Lms LED128 - 128W LED 12800 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K	Mount AC50 - 50” Aircraft Cable PDXX - Pendant Mount Replace XX with desired length of pendant rods	Outer Row (Sides) PER - Perforated LV - Louvered (T5 only)	Length Multiples of 4’ 4 - 4 Foot XX - Multiples of 4 Foot	Options DV - 120/277 Dual Volt MOT - Motion Sensor EM - Emergency Backup EM5 - 500 Lm Emergency EM12 - 1200 Lm Emergency DIM0-10V - 0-10V Dimmable