

Standard Product Specifications

**Materials:**

Die-Formed Heavy Gauge Painted  
Cold-Rolled Steel Housing

**Finish:**

Powder Coated

**Lens:**

White Opal Acrylic Diffuser

**LED:**

Integrated LED Array

**Listing:**

Dry List to Meet UL 1598 Standard

**Driver Info:**

120/277V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS:**

11"W x 4"H x 48"L

11"W x 4"H x 96"L

11"W x 4"H x **XX**"L (Custom Length)



**DISCONTINUED**  
**LIMITED STOCK AVAILABLE -**  
**CALL CUSTOMER SERVICE FOR DETAILS**

MODEL	LENGTH	FINISH	WATTAGE	KELVIN	MOUNT	OPTIONS
<b>Model</b> DIPERF	<b>Length</b> 4 - 4 Foot 8 - 8 Foot <b>XX</b> - Custom Length (In Multiples of 4 Feet)	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage</b> LED60 - 60W LED 6000 Lms LED84 - 84W LED 8400 Lms	<b>Kelvin</b> 30 - 30K 35 - 35K 40 - 40K 50 - 50K	<b>Mount</b> AC50 - 50" Aircraft Cable Mount AC <b>XX</b> - Aircraft Cable Mount Replace <b>XX</b> with Desired Length in Inches	<b>Options</b> DIM - 0-10V Dimmable EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency