

Standard Product Specifications

Materials:
Steel Housing
Finish:
Powder Coated
Lens:
White Polycarbonate
LED:
Integrated LED Array

Listing:
Dry List to Meet UL 1598 Standard
Driver Info:
120V
Installation Information:
Install by Qualified Electrician
Warranty:
2 Years From Date of Shipment

DIMENSIONS:
8" W x 3" H x 48" L
8" W x 3" H x 96" L
8" W x 3" H x **XX**" L (Custom Length)



MODEL	LENGTH	FINISH	WATTAGE	KELVIN	MOUNT	OPTIONS
Model DISQ48	Length 4 - 4 Foot Length 8 - 8 Foot Length XX - Custom Length (In Multiples of 4 Feet)	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED60 - 60W LED 6000 Lms LED84 - 84W LED 8400 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	AC50 - 50" Aircraft Cable	Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency SLT - Slotted Polycarbonate Lens LVR - Louvers