

Standard Product Specifications

**Materials:**

Extruded Aluminum Tubing

**Finish:**

Powder Coated

**Lens:**

Polycarbonate Options

**LED:**

Integrated LED Array

**Listing:**

Wet List to Meet UL 1598 Standard

**Driver Info:**

120V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS:**

**DNCSQ612** - 6”Sq. x 12”H

**DNCSQXX** - XX”Sq. x XX”H

(Custom Width and Height)



MODEL	FINISH	WATTAGE	KELVIN	LENS	OPTIONS
<b>Model</b> DNCSQ612 DNCSQXX	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage</b> LED5 - 5W LED 500 Lms LED10 - 10W LED 1000 Lms LED15 - 15W LED 1500 Lms	<b>Kelvin</b> 30 - 30K 35 - 35K 40 - 40K 50 - 50K	<b>Lens</b> WP - White Polycarbonate FP - Frosted Polycarbonate	<b>Options</b> DV - Dual Volt 120/277V DIM - 0-10V Dimmable PMXX - Pendant Mount Replace XX with Pendant Length in Inches CMXX - Cord Mount Replace XX with Cord Length in Inches