

POLE LIGHTS
DPL46/DPL46S

Standard Product Specifications

Materials:

Aluminum Housing

Finish:

Powder Coated

Lens:

White Polycarbonate

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

DPL46: Top - 46”L x 6”W x 4”H

Pole - 6” Depth x 6”W

DPL46S: Top - 46”L x 6”W x 4”H

Pole - 4”Depth x 6”W

(Pole Heights Custom - Contact Customer Service)



Shown With Single Head



Shown With Two Heads



MODEL	FINISH	WATTAGE	KELVIN	MOUNTING	TYPE	OPTIONS
Model DPL46 DPL46S	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED40 - 40W LED 4000 Lms LED60 - 60W LED 6000 Lms LED80 - 80W LED 8000 Lms (Each Head)	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Mounting 190 - 1 Head @ 90 Degrees 290 - 2 Heads @ 90 Degrees 2180 - 2 Heads @ 180 Degrees 390 - 3 Heads @ 90 Degrees 490 - 4 Heads @ 90 Degrees	Type III - Type III IV - Type IV V - Type V	Options DIM - 0-10V Dimmable PC - Photocell MOT - Motion Sensing EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency