

CEILING FLUSH/WALL SCONCE DSQ

DIVINE LIGHTING
FABRICATION & POWDER COATING LLC

Standard Product Specifications

Materials:

Galvanized Steel Housing

Finish:

Powder Coated

Lens:

White Polycarbonate

LED:

Integrated LED Array

Listing:

Damp List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

DSQ8 - 8.4"W x 8.4"H x 3"E

DSQ11 - 10.6"W x 10.6"H x 3.07"E



PATTERN 1



PATTERN 2



PATTERN 3



PATTERN 4

MODEL	PATTERN	FINISH	WATTAGE	KELVIN	OPTIONS
Model DSQ8 DSQ11	Pattern 1 - Open 2 - X-Bar 3 - Grill 4 - Eyelid	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(DSQ8) LED5 - 5W LED 500 Lms LED10 - 10W LED 1000 Lms Wattage(DSQ11) LED10 - 10W LED 1000 Lms LED15 - 15W LED 1500 Lms	Kelvin 30 - 30K 40 - 40K	Options DV - Dual Volt 120/277V

Divine Lighting Fabrication & Powder Coating, LLC.
Conroe, TX

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 12323 1425 ACE