

FLOODLIGHTS EFL SERIES

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

Tempered Glass

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

0-10V Dimmable Standard

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

(Does not Include Mounting Hardware)

EFLS - 7"W x 5"H x 3"D

EFLM - 10.5"W x 7"H x 3"D

EFL - 14"W x 9"H x 3.25"D



EFLS



EFLM



EFL

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
		Wattages are CCT Selectable		
Model EFLS EFLM EFL	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(EFLS) LED15 - 15W LED 2064-2224 Lms LED25 - 25W LED 3258-3480 Lms LED35 - 35W LED 4507-4796 Lms Wattage(EFLM) LED50 - 50W LED 6909-7415 Lms LED70 - 70W LED 9085-9777 Lms LED90 - 90W LED 10967-11896 Lms Wattage(EFL) LED105 - 105W LED 14099-15148 Lms LED120 - 120W LED 15591-16590 Lms LED150 - 150W LED 19557-20793 Lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Options KN - Knuckle Mount YOKE - Yoke Mount SF - Slip Fitter Mount* *EFL Only