

Standard Product Specifications

**Materials:**

Die-Cast Aluminum

**Finish:**

Powder Coated

**Lens:**

Clear Polycarbonate

**LED:**

Integrated LED Array

**Listing:**

Wet List to Meet UL 1598 Standard

**Driver Info:**

120/277V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS:**

15.75”Dia. x 23.19”H



DARK SKY  
COMPLIANT



MODEL	FINISH	WATTAGE	KELVIN	LENS	TYPE	OPTIONS
<b>Model</b> EPTS101B	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage</b> LED25 - 25W LED 2500Lms LED35 - 35W LED 3500Lms LED60 - 60W LED 6000Lms LED80 - 80W LED 8000Lms	<b>Kelvin</b> 30 - 30K 35 - 35K 40 - 40K 50 - 50K	<b>Lens</b> CP - Clear Polycarbonate FP - Frosted Polycarbonate*  *Only available without optics	<b>Type (CP Only)</b> II - Type II III - Type III IV - Type IV V - Type V	<b>Options</b> DIM - 0-10V Dimmable PC - Photocell MOT - Motion Sensor