

Standard Product Specifications

Materials:
Die-Cast Aluminum Housing
Finish:
Powder Coated
Lens:
Clear Acrylic
LED:
Integrated LED Array

Listing:
Wet List to Meet UL 1598 Standard
Driver Info:
120/277V
Installation Information:
Install by Qualified Electrician
Warranty:
2 Years From Date of Shipment

DIMENSIONS:

(Does Not Include Arms)

FLMS - 6"W x 3.8"H x 2.6"E (ADA)
FLMM - 7.95"W x 4.8"H x 3.1"E (ADA)
FLML - 11"W x 6.1"H x 4.9"E
FLMXL - 14.5"W x 12.6"H x 4.4"E



MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model FLMS FLMM FLML FLMXL	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(FLMS) LED15 - 15W LED 2000 Lms LED27 - 27W LED 3600 Lms Wattage(FLMM) LED45 - 45W LED 5650 Lms LED60 - 60W LED 7450 Lms Wattage(FLML) LED70 - 70W LED 9300 Lms LED90 - 90W LED 12400 Lms Wattage(FLMXL) LED135 - 135W LED 18000 Lms LED200 - 200W LED 26000 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Options DIM - 0-10V Dimmable PC - Photocell YOKE - Yoke Mount SF - Slip Fitter KNL - Knuckle WM - Wall Mount