

Standard Product Specifications

**Materials:**

Cast Aluminum Housing

**Finish:**

Powder Coated

**Lens:**

Tempered Glass

**LED:**

Integrated LED Array

**Listing:**

Wet List to Meet UL 1598 Standard

**Driver Info:**

120/277V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS:**

**GBLLT1** - 5.5" Face Dia. x 8.78"E (Without Knuckle)

With Knuckle - 3.5"H

**GBLLT2** - 4" Sq. Face x 6.69"E (Without Knuckle)

With Knuckle - 3"H



**GBLLT1**



**GBLLT2**



**FMS**

| MODEL                            | FINISH  | WATTAGE                                    | KELVIN                    | OPTIONS  |
|----------------------------------|---|--|---------------------------|--|
| <b>Model</b><br>GBLLT1<br>GBLLT2 | <b>Finish</b><br>DB - Dark Bronze<br>BL - Black<br>AS - Anodized Silver<br>WH- White<br>CC - Custom Color | <b>Wattage</b><br>LED12 - 12W LED 1000 Lms | <b>Kelvin</b><br>50 - 50K | <b>Options</b><br>JB - Junction Box Mount<br>FMS - Flood Mounting Stake<br>KN - Knuckle (Standard) |