

Standard Product Specifications

**Materials:**

Die-Cast Aluminum Housing

**Finish:**

Powder Coated

**Lens:**

Tempered Glass

**LED:**

Integrated LED Array

**Listing:**

Wet List to Meet UL 1598 Standard

**Driver Info:**

120/277V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS(Does Not Include Mounting):**

**30W** - 6.875"W x 5.4"H

**60W/80W** - 9.25"W x 7.0625"H

**150W** - 14.75"W x 8.75"H



60°



80°



100°

**Beam Angle Options**

MODEL	FINISH	WATTAGE	KELVIN	BEAM ANGLE	OPTIONS
<b>Model</b> <b>GFL</b>	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	<b>Wattage (CCT Selectable)</b> <b>LED30</b> - 30W LED 3990 Lms (CCT 10/20/30W) <b>LED60</b> - 60W LED 8779 Lms (CCT 30/45/60W) <b>LED80</b> - 80W LED 11816 Lms (CCT 40/60/80W) <b>LED150</b> - 150W LED 23255 Lms (CCT 105/120/150W)	<b>Kelvin (CCT Selectable)</b> 30 - 30K 40 - 40K 50 - 50K	<b>Beam Angle</b> 60 Degrees 80 Degrees 100 Degrees	<b>Options</b> PC - Photocell SF - Slip Fitter TR - Trunnion KN - Knuckle