

**CEILING FLUSH
GLM SERIES**

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

High Temperature Acrylic Options

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

GLM10 - 9.52”Sq. x 3.19”E

GLM12R (30W, 45W, 60W) - 12”Dia. x 3.32”E

GLM12R (90W) - 13”Dia. x 3.15”E



GLM10



GLM12R

MODEL	FINISH	WATTAGE	KELVIN	LENS	OPTIONS
Model GLM10 GLM12R(Round)	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage(GLM10) LED40 - 40W LED 5400 Lms LED70 - 70W LED 8000 Lms Wattage(GLM12R) LED30 - 30W LED 3800 Lms LED45 - 45W LED 5800 Lms LED60 - 60W LED 7200 Lms LED90 - 90W LED 11600 Lms	Kelvin 40 - 40K 50 - 50K	Lens(GLM10) CP - Clear Polycarbonate Lens(GLM12R) FP - Frosted Polycarbonate	Options DIM - 0-10V Dimmable PC - Photocell MOT - Motion Sensing EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency