

Standard Product Specifications

**Materials:**

Die-Cast Aluminum Housing

**Finish:**

Powder Coated

**Lens:**

High Temperature Acrylic Options

**LED:**

Integrated LED Array

**Listing:**

Wet List to Meet UL 1598 Standard

**Driver Info:**

120/277V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment

**DIMENSIONS:**

GLM12R (30W, 45W, 60W) - 12”Dia. x 3.32”E

GLM12R (90W) - 13”Dia. x 3.15”E



MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
<b>Model</b> GLM12R(Round)	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	<b>Wattage</b> LED30 - 30W LED 3800 Lms LED45 - 45W LED 5800 Lms LED60 - 60W LED 7200 Lms LED90 - 90W LED 11600 Lms	<b>Kelvin</b> 50 - 50K	<b>Options</b> DIM - 0-10V Dimmable PC - Photocell MOT - Motion Sensing EM5 - 500 Lms Emergency* EM10 - 1000 Lms Emergency EM12 - 1200 Lms Emergency* <b>*Back Box Required</b>