

Standard Product Specifications

Materials:
20ga. G90 Galvanized Steel
Finish:
Powder Coated
Lens:
White Polycarbonate
Lens Placement:
Bottom Lens Standard, Side Lenses
Optional
LED:
Integrated LED Array

Listing:
Damp List to Meet UL 1598 Standard
Driver Info:
120/277V
Installation Information:
Install by Qualified Electrician
Warranty:
2 Years From Date of Shipment

DIMENSIONS:
LMC24 - 2.5"W x 4"H
LMC33 - 3"W x 3"H
LMC34 - 3"W x 4"H
LMC44 - 4"W x 4"W
LMC45 - 4"W x 5"H



Continuous Runs in Max 8 Foot Sections

MODEL	LENGTH	FINISH	WATTAGE	KELVIN	LENS PLACEMENT	OPTIONS
Model LMC24 LMC33 LMC34 LMC44 LMC45	Length 4' - 4 Foot 8' - 8 Foot	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(4 Foot) LED40 - 40W LED 4000 Lms LED64 - 64W LED 6400 Lms Wattage(8 Foot) (2)LED40 - (2) LED40W 8000 Lms (2)LED64 - (2) LED64W 12800 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Lens Placement(Optional) SL - Side Lenses 3L - Lenses on Bottom and Sides	Options DIM - 0-10V Dimmable EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency MOT50 - Programmable Lighting System 10-90% Dimmable AC50 - 50" Aircraft Cable