

# LINEAR LRC SERIES

## Standard Product Specifications

### Materials:

20ga. G90 Galvanized Steel

### Finish:

Powder Coated

### Lens:

White Polycarbonate

### LED:

Integrated LED Array

### Listing:

Damp List to Meet UL 1598 Standard

### Driver Info:

120V

### Installation Information:

Install by Qualified Electrician

### Warranty:

2 Years From Date of Shipment

### DIMENSIONS:

**LRC23** - 2"W x 3"H

**LRC43** - 4"W x 3"H

**LRC44** - 4"W x 4"H

**LRC55** - 5"W x 5"H

(Custom Sizes Available - Call Customer Service)



MODEL	LENGTH	FINISH	WATTAGE	KELVIN	OPTIONS
<u>Model</u> <b>LRC23</b> <b>LRC43</b> <b>LRC44</b> <b>LRC55</b> <b>LRCXX</b> Replace XX with Width and Depth in Inches	<u>Length</u> 3' - 3 Foot 4' - 4 Foot 6' - 6 Foot 8' - 8 Foot	<u>Finish</u> <b>DB</b> - Dark Bronze <b>BL</b> - Black <b>AS</b> - Anodized Silver <b>WH</b> - White <b>CC</b> - Custom Color	<u>Wattage(3 Foot)</u> <b>LED23</b> - 23W LED 2300 Lms  <u>Wattage(4 Foot)</u> <b>LED36</b> - 36W LED 3600 Lms  <u>Wattage(6 Foot)</u> <b>LED46</b> - 46W LED 4600 Lms  <u>Wattage(8 Foot)</u> <b>LED36</b> - 36W LED 3600 Lms <b>LED64</b> - 64W LED 6400 Lms	<u>Kelvin</u> <b>30</b> - 30K <b>35</b> - 35K <b>40</b> - 40K <b>50</b> - 50K	<u>Options</u> <b>DV</b> - Dual Volt 120/277V <b>DIM</b> - 0-10V Dimmable <b>DIM50</b> - 50% Dimming <b>EM5</b> - 500 Lms Emergency <b>EM10</b> - 1000 Lms Emergency <b>EM12</b> - 1200 Lms Emergency