

Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

Clear Polycarbonate

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

MWPCSLs - 13.1"W x 9.6"H x 3.8"E (ADA)

MWPCSLl - 13.1"W x 9.6"H x 5"E (Not ADA)



MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model MWPCSLs MWPCSLl	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED26 - 26W LED 3800 Lms LED38 - 38W LED 5600 Lms LED65 - 65W LED 9500 Lms LED100 - 100W LED 14800 Lms LED135 - 135W LED 19000 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Options DIM - 0-10V Dimmable PC - Photocell EM5 - 500 Lms Emergency EM10 - 1000 Lms Emergency EM12 - 1200 Lms Emergency