

Standard Product Specifications

**Materials:**  
Die-Cast Aluminum Housing  
**Finish:**  
Powder Coated  
**Lens:**  
Clear Polycarbonate  
**LED:**  
Integrated LED Array

**Listing:**  
Wet List to Meet UL 1598 Standard  
**Driver Info:**  
120/277V  
**Installation Information:**  
Install by Qualified Electrician  
**Warranty:**  
2 Years From Date of Shipment  
5 & 7 Year Warranties Available

**DIMENSIONS:**

MWPCSL S - 13.1"W x 9.6"H x 3.8"E (ADA)  
MWPCSL L - 13.1"W x 9.6"H x 5"E (Not ADA)



MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
<b>Model</b> MWPCSL S MWPCSL L(100W & 135W)	<b>Finish</b> DB - Textured Bronze BL - Textured Black AS - Textured Silver WH - Textured White CC - Custom Color	<b>Wattage</b> LED26 - 26W LED 3800 Lms LED38 - 38W LED 5600 Lms LED65 - 65W LED 9500 Lms LED100 - 100W LED 14800 Lms* LED135 - 135W LED 19000 Lms** *Other Wattages Available - Contact Customer Service for More Details **LED135 Available in 40K and 50K Only	<b>Kelvin</b> 30 - 30K 40 - 40K 50 - 50K	<b>Options</b> 5Y - 5 Year Warranty 7Y - 7 Year Warranty DIM - 0-10V Dimmable PC - Photocell EM10 - 1000 Lms Emergency* *Not Available in 100W or 135W