

**CEILING FLUSH**  
**NAUTICAL SERIES**

Standard Product Specifications

**Materials:**  
 Aluminum Housing  
**Finish:**  
 Powder Coated  
**Lens:**  
 White Acrylic  
**LED:**  
 Integrated LED Array

**Listing:**  
 Wet List to Meet UL 1598 Standard  
**Driver Info:**  
 120V  
**Installation Information:**  
 Install by Qualified Electrician  
**Warranty:**  
 2 Years From Date of Shipment

**DIMENSIONS:**

**NAU52** - 5.85”Dia. x 2.56”E  
**NAU83** - 8.65”Dia. x 3.15”E  
**NAU103** - 10.82”Dia. x 3.39”E  
**NAU145** - 14.17”Dia. x 5.82”E (Not ADA)



**Open Face**



**Cross Face**



**Cage Face**



**Eyelid Face**



**Eyelid Face w/ Bar**



**3 Bar Face**

MODEL	FACE	FINISH	WATTAGE	KELVIN	OPTIONS
<b>Model</b> NAU52 NAU83 NAU103 NAU145	<b>Face</b> OP - Open Face CR - Cross Face CG - Cage Face EB - Eye Face w/ Bar 3B - 3 Bar Cross Face EYE - Eyelid Face	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage(NAU52 &amp; NAU83)</b> LED10 - 10W LED 1000 Lms LED15 - 15W LED 1500 Lms  <b>Wattage(NAU103 &amp; NAU145)</b> LED15 - 15W LED 1500 Lms LED20 - 20W LED 2000 Lms	<b>Kelvin</b> 30 - 30K 40 - 40K	<b>Options</b> DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM5 - 500 Lms Emergency* EM12 - 1200 Lms Emergency* *EM Only Available in NAU145