

POLE POLES



DIMENSIONS:

- RSP** - Base 10"
- Shaft** - 3 or 4"
- SSP** - Base 10" (4")
- SSP** - Base 12" (5")
- Shaft** - 4"sq. or 5"sq

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

A Square Post

Materials:

Milled Steel

Finish:

Powder Coated

Anchor Bolts:

See Chart

Template:

Provided

Hand Hole:

Standard on Poles 10' and Taller

Base Cover:

Standard on all Poles

Listing:

Wet List to Meet UL 1598 Standard

Installation Information:

Install by Qualified Electrician

Anchor Bolts
includes (4) black iron bolts
w/ 2 nuts and 2 washers each

5/18" x 18"
3"RSP up to 15'

3/4" x 30"
4"RSP 21'-25'
4"SSP over 25'

3/4" x 18"
3"RSP 16'-20'
4"SSP up to 25"

1" x 36"
5"SSP over 20'



RSP



SSP



DB-SSP



TENON



3" 2 3/8 Adapter



GFCI




COVER
(Comes Standard with
Anchored Poles)



Square Pole Top Cover



Hand Hole Cover



Eye Hooks

ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	SHAFT	SCHEDULE/GAUGE	HEIGHT	OPTIONS	FINISH
Model POLE-RSP - Round Steel Anchor Plate POLE-SSP - Square Steel Anchor Plate POLE-DB-SSP - Square Steel Direct Bury POLE-DB-RSP - Round Steel Direct Bury POLE-DB-AL - Round Aluminum Direct Bury	Shaft 3 - 3"OD (Round) 4 - 4"OD (Round) 4 - 4" (Square) 5 - 5" (Square)	Schedule/Gauge 40 - Schedule 40 7 - 7 Gauge 11 - 11 Gauge .125 - Gauge* *Aluminum Only	Height 8 - 8ft 10 - 10ft 12 - 12ft 15 - 15ft 18 - 18ft 20 - 20ft 22 - 22ft 25 - 25ft 30 - 30ft XX - Custom Height	Options HH - Hand Hole (Steel) 190 - (1)90 Deg Hole 290 - (2)90 Deg Hole 390 - (3)90 Deg Hole 490 - (4)90 Deg Hole 280 - (2)180 Deg Hole GFCI - GFCI Recepticle GFCILOCK - GFCI Lock TENON23/8x3 TENON27/8x3 EYE - Eye Hooks SM - Smooth *Aluminum Only	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color