

SITE LIGHTING PSLS / PSL



DIMENSIONS:

PSLS 3.5”H x 13”W x 17.5”E (No Arm)
5.6”W x 13”W x 25.2”E (Staright Arm)
PSL 3.5”H x 13”W x 21.1”E (No Arm)
5.6”W x 13”W x 28.8”E (Staright Arm)

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Flat Top Site Light with Low to High Output

Materials:

Die Cast Aluminum Housing

Finish:

Powder Coated

Lens:

Heat-Resistant Clear Polycarbonate

LED:

Integrated LED Array

Listing:

Wet List to Meet UL1598 Standard

IP65 Rated

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	TYPE	OPTIONS
Model PSLS PSL	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage (PSLS) LED70 - 70W LED 9300-10000 lms LED100 - 100W LED 12300-13500 lms LED150 - 150W LED 17700-18500 lms LED180 - 180W LED 20600-21500 lms Wattage (PSL) LED220 - 220W LED 30200-31000 lms LED310 - 310W LED 36800-38400 lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Type III - Type III IV - Type IV V - Type V* *Standard	Options PC - Photocell MOT - Motion DIM0-10 - 0-10V Dimmable TRUN - Trunnion Mount LSF - Large Slip Fitter MA - Mounting Arm SF - Slip Fitter