

Standard Product Specifications

Materials:
Cast Aluminum Houston
Finish:
Powder Coated
Lens:
Clear Polycarbonate
Vandal-Resistant
LED:
Integrated LED Array

Listing:
List to Meet UL 1598 Standard
Driver Info:
120/277V
Installation Information:
Install by Qualified Electrician
Warranty:
2 Years From Date of Shipment

DIMENSIONS:
QSL32 - 18”Dia. x 8.5”H x 23.25”E



| MODEL | FINISH | WATTAGE | KELVIN | TYPE | OPTIONS |
|-----------------------|---|---|--|---|---|
| Model QSL32 | Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color | Wattage LED37 - 37W LED 5400 Lms LED65 - 65W LED 9600 Lms LED100 - 100W LED 14800 Lms LED140 - 140W LED 20000 Lms <i>*Lower lumen output on type IV</i> | Kelvin 30 - 30K* 40 - 40K 50 - 50K <i>*37W & 65W Only</i> | Type II - Type 2 III - Type 3 IV - Type 4 V - Type 5 | Options DIM0-10 - 0-10V Dimmable MOT - Motion Sensor PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency |