CEILING FLUSH SATURN SERIES



Standard Product Specifications

Materials: Steel Pan and Rings Finish: Powder Coated Lens: White Acrylic LED: Integrated LED Array Listing: Wet List to Meet UL 1598 Standard **Driver Info:** 120V **Installation Information:** Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

DIMENSIONS:

SAT10 - 10"Dia. x 3.75"H SAT12 - 12"Dia. x 3.75"H **SAT14** - 14"Dia. x 3.75"H **SAT16** - 16"Dia. x 4.5"H SAT18 - 18"Dia. x 4.5"H





MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model SAT10 SAT12 SAT14 SAT16 SAT18	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage(SAT10 & SAT12) LED18 - 18W LED 1800 Lms Wattage(SAT14) LED24 - 24W LED 2400 Lms Wattage(SAT16) LED28 - 28W LED 2800 Lms Wattage(SAT18) LED35 - 35W LED 3500 Lms	<u>Kelvin</u> 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Options DV - Dual Volt 120/277V EM14 - 1400 Lms Emergency
Divine Lighting Fabrication & Powder Coating, LLC.		http://www.divinelighting.net		PH: 936-494-3900

Conroe, TX

customerservice@divinelighting.net

FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice