

Standard Product Specifications

Materials:
Aluminum
Finish:
Powder Coated
Lens:
Acrylic
LED:
Integrated LED Array
Mounting
Pendant Rods (Standard)

Listing:
Dry List to Meet UL 1598 Standard
Driver Info:
120V
Installation Information:
Install by Qualified Electrician
Warranty:
2 Years From Date of Shipment

DIMENSIONS:

SWC26 - 26" Dia. x 7"H x OAHXX*

SWC30 - 30"Dia. x 8"H x OAHXX*

*OAHXX - Over All Height in Inches



MODEL	FINISH	WATTAGE	KELVIN	LENS	OPTIONS
Model SWC26 SWC30	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED40 - 40W LED 4000 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Lens AL - Alabaster EM - Earth Marble ET - Etruscan HO - Honey Onyx IV - Ivory LB - Lapis Blue MG - Malachite Green M- Mica NH - Natural Horn NM - New Mica T - Teastain W - White WD - White Drop WS - White Swirl	Options DIMM - Dimmable 0-10V DV - Dual Volt 120/277V OAHXX - Overall All HeightXX In Inches PR - Pendant Rod (Standard) AC - Aircraft Cable In Inches