

WALL SCONCE

UPW



**DIMENSIONS:**  
 UPW7 - 4.5"W x 7"H x 7"D  
 UPW9 - 6"W x 9"H x 8.5"D  
 UPW612 - 6"W x 12"H x 8.5"D  
 UPW615 - 6"W x 15"H x 8.5"D  
 UPW618 - 6"W x 18"H x 8.5"D  
 UPW812 - 8"W x 12"H x 8.5"D  
 UPW815 - 8"W x 15"H x 8.5"D  
 UPW1015 - 10"W x 15"H x 8.5"D

|              |  |
|--------------|--|
| Project:     |  |
| Location(s): |  |
| Type:        |  |
| Qty:         |  |
| Date:        |  |

Custom sizes available

PRODUCT SPECIFICATIONS

**Description:**  
 Aluminum Cylinder Uplight

**Materials:**  
 Aluminum Housing

**Finish:**  
 Powder Coated

**Lens:**  
 Frosted Polycarbonate

**LED:**  
 Integrated LED Array

**Listing:**  
 Wet List to Meet UL 1598 Standard

**Driver Info:**  
 120V

**Installation Information:**  
 Install by Qualified Electrician

**Warranty:**  
 2 Years From Date of Shipment



ORDER INFORMATION  
 Call Factory For Fluorescent Options

| MODEL  | FINISH   | WATTAGE  |  | KELVIN  | OPTIONS   |
|--|--|--|--|---|---|
| <b>Model</b><br>UPW7<br>UPW9<br>UPW612<br>UPW615<br>UPW618<br>UPW812<br>UPW815<br>UPW1015<br>UPWXXXX | <b>Finish</b><br>DB - Dark Bronze<br>BL - Black<br>AS - Anodized Silver<br>WH - White<br>CC - Custom Color | <b>Wattage (4.5"W -6"W)</b><br>LED10 - 10W LED 1000Lms<br>LED15 - 15W LED 1500Lms<br>LED20 - 20W LED 2000Lms<br>LED25 - 25W LED 2500Lms<br><br><b>Wattage(8"W)</b><br>LED15 - 15W LED 1500Lms<br>LED20 - 20W LED 2000Lms<br>LED25 - 25W LED 2500Lms<br>LED30 - 30W LED 3000Lms | <b>Wattage (10")</b><br>LED20 - 20W LED 2000 Lms<br>LED30 - 30W LED 3000 Lms<br>LED45 - 45W LED 5800 Lms | <b>Kelvin</b><br>30 - 30K<br>35 - 35K<br>40 - 40K<br>50 - 50K | <b>Options</b><br>DV - 120/277 Dual Volt<br>DIM - 0-10V Dimmable<br>NTXX - Narrow Throw<br>*fill in XX for Beam Angle<br>LT - Lens Top (Standard)<br>EM5 - 500 Lm Emergency*<br>EM12 - 1200 Lm Emergency*<br>*requires 15"H minimum |